

# SHERA SEALANT PU



## Product Description

Fast-setting single-component polyurethane elastomeric sealant that dries in contact with air and moisture. It forms a joint between the sheets of high elasticity, high resistance to tearing, atmospheric agents and UV rays.

Category 25E.

SHERA SEALANT PU 25 has the CE marking for application as a sealant for facade elements for indoor and outdoor applications used in cold climates EN 15.651-1 ( F EXT - INT CC )

## Applications

For bonding the joint between the SHERA BOARD slabs.

The surface must be dry and clean, free of dust, grease or other contaminants.

Apply with a manual gun.

After application, smooth the joint with water and soap with a spatula.

This product should be used within 24 hours after the cartridge or pocket protector is opened.

During polymerization, avoid contact with MS polymers, silicones or polymerized PU hybrid as well as with alcohols or ammonia.

Do not apply at a temperature below 5 ° C.

Features	U. M.	Value
Base	-	Single-component polyurethane
Elongation at break	%	≥250 (ASTM D 412)
Appearance	-	Milky white liquid
Packagging	l	4
pH	-	7 ca.
Coverage	m <sup>2</sup> /l	10/15
Mixing ratio		Ready to use primer

Technical Data Sheet

FIBRAN reserves the right to alter or amend product specifications without notice. The information included in this publication is correct to the best of our knowledge at the time of printing. Whilst FIBRAN will endeavour to ensure publications are up to date, it is the user's responsibility to check with the company the validity of the information prior to materials' use. For more information visit the web site [www.fibran.it](http://www.fibran.it).

Date 31/07/2018